

Specification: Sideconnect Starter Kit

Product Code	Sideconnect starter kit 15 mm x 15 mm	Sideconnect starter kit 15 mm x 30 mm
Max. operating pressure	10 bar (145 psi)	
Dimensions assembly tool	85 mm x 54 mm x 24 mm	
Material assembly tool	Aluminium	
Dimensions mounting frame	128 mm x 86 mm x 4 mm	
Material mounting frame	Aluminium	
Body and connectors	Body and connectors for 15 mm x 15 mm chips	Body and connector for 15 mm x 30 mm chips
Material body and connectors	PEEK (Polyetheretherketone)	
Dimensions connectors	25 mm x 7 mm x 4 mm	
Number of Inlets	4 inlets	
Number of outlets	4 outlets	
Compatible to tubing with diameter	Compatible with 1/16 inch tubing	
Clamps	2 aluminium clamps	
Srew driver	1 Screw driver with a 35 mm blade	
Screws	5 screws with M2 thread, lenght 8 mm	
Contents	ETFE tubing and 5 FFKM ferrules	
Length	1.5 m	
Outer Diameter (OD)	1/16 inch	
Inner Diameter (ID)	200 µm	
Material	Tube: ETFE (Ethylene tetrafluoroethylene), Ferrules: FFKM (Perlast) perfluoroelastomer	

